Seuic

PRODUCT SPEC SHEET

AUTOID 3P MOBILE COMPUTERS

AUTOID 3P

Creating a new digital assistant for enterprise

AUTOID 3P, equipped with a high-performance core and an enterprise-level management system, guarantees long-term stability, while affordable at the same time. The redesigned diamond-shaped oversized scan button and extra-large key makes operation smoother, and the highquality 2W loud speaker is a plus benefit for workers in noise environment, Wireless communication ensures fast data transmission and featuring Seuic's newest industrialgrade scanning engine makes recognition of 1D and 2D codes faster than ever.



Product Features



Handy to hold and Easy to put into your pocket

Thanks to its ergonomic design, with the optimized golden grip curvature, users can hold the product for extended periods without feeling fatigued. In addition, because of its lightweight, streamlined design, it is easy to handle and carry.



More durable, effectively reducing business costs

The IP65 seal and 1.5m drop protection level reduce the failure rate. In addition, the removable battery allows staff to switch shifts within a reasonable time.

PRODUCT SPEC SHEET AUTOID 3P MOBILE COMPUTER

Specifications

Physical Characteris	tics
Dimensions	6.2 in. L x 2.6 in. W x 0.7 in. H
	159 mm L x 66.3 mm W x 18.9 mm H
Weight	9.3 oz./265 g (include battery)
Display	4.0 inch industrial grade low temperature resistant
	IPS screen, 480(RGB)×800 (WVGA)
Touch Panel	Capacitive touch, dual mode touch-with or without
	a thick glove/with or without wet hand
Power	Detachable 3.85V rechargeable 5200mAh Li-ion
	battery
	Side Type-C interface, intelligent identification of PC
	and charger, Bottom contact tail plug interface:
	supports 5V/2A charging
Expansion Slot	Micro SD Card, compatible up to 256GB
Interface/	Support Type-C, support OTG
Communication	
Notifications	Sound, vibrator, LED light indicator
Keypad	25 Keys, LED (buttons with backlight)
Voice and Audio	Built-in speaker, Built-in microphone, Type-C Support
	headphones
	support VoLTE Function
Performance Characteristics	
CPU	MTK Octa-core 2.0GHz
Operating System	Android 12.0
Memory	4GB RAM/64GB ROM
User Environment	
Operating Temp.	-4 °F to 131 °F/-20 °C to +55 °C
Storage Temp.	Battery excluded: -40 °F to 158 °F/-40 °C to +70 °C
Humidity	5% to 95% RH, non-condensing
Drop Spec.	Multiple 4.9 ft./1.5 m drops to concrete at room
	temperature
Tumble Spec.	1000 rounds of tumble from 1.6 ft./0.5 m, equals to
	2000 impacts

-	
Sealing	IP65
Electrostatic	±15 kV air discharge, ±8 kV direct discharge
Discharge (ESD)	
Data Capture	
Scanning	Seuic 2D image scan engine
	Camera scanning
Camera	Rear: 13MP Autofocus, Maximum resolution: 4224 *
	3136,1080P@30fps(taking vedio)
	Flashlight is supported, and torch light can be used
Wireless Connectivity	
WLAN Radio	IEEE 802.11ac/a/b/g/n/d/e/h/i/j/k/r/v/w (2.4 G/5G
	dual-frequency WIFI)
	Depends on different countries(regions), 2.4GHz:
	2.412GHz~2.472GHz; 5GHz: 5.17GHz~5.825GHz
WWAN Radio	GSM: Quad Band (900, 1800Mhz)
	TD-SCDMA: Band34, Band39
	WCDMA: Band1, Band5, Band8
	CDMA 1x/EVDO: BCO
	TDD-LTE: Band34, Band38, Band39, Band40, Band41
	FDD-LTE: Band1, Band3, Band5, Band8
GPS	GPS + GLONASS + Beidou + Galilieo, support AGPS
	Frequency
	GPS: L1 (1.575 GHz); Beidou: B1 (1.561 GHz);
	GLONASS: L1 (1.602 GHZ)
Accessories	
Standard	Power Adapter, USB Cable, Battery, Hand Strap
Additional	Protective case, 4-slot battery charger, Single device
	charging cradle
Third Party Application Development Support	
System Software	Android 12
System	Eclipse, Android Studio
Programming	
Environment	
	•

